

Lyman®

Sighting Products

Ideal for Lyman Great Plains, Trade, Deerstalker and Other European Muzzleloaders. These bright, light-gathering sights will fit most black powder rifles with 15/16" octagon barrels and approximately .360" wide dovetails.

MOUNTING INSTRUCTIONS:

Rear Sight - Remove old sight from rifle. (*Drift out sight from left to right*). Loosen set screw on side of rear sight and remove top two slides from base. Remove dovetail wedge from rear sight base by removing hold down screw. Slide dovetail wedge into barrel dovetail. Position rear sight base over dovetail wedge. Insert screw and tighten securely. Reinstall top two slides onto sight base.

Front Sight - Remove old sight from rifle. (*Drift out sight from left to right*). Start the new sight into the dovetail from the right hand side and tap into place using a brass rod or piece of hard wood.

NOTE: *Dovetail dimensions can vary. The sight may need to be filed to fit barrel dovetail.*

REAR SIGHT ADJUSTMENT:

Adjust for windage by loosening the top set screw and moving the top slide the direction that you want the bullet to go. Adjust for elevation by loosening the set screw in the middle slide and move the top two slides in the direction that you want the bullet to go.

Lyman

Part No.3090145



User Information

Fiber Optic Sight Installation

Two dovetail wedges have been supplied with this sight set. One is smaller than the other, to allow easier fitting for a variety of barrels. Lyman muzzleloaders made after 2001 have slightly smaller dovetails than earlier muzzleloaders. It is ok for the rear sight wedge to slide easily into the dovetail, as long as the sight tightens securely against the barrel. The front sight may require filing to fit various size dovetails.